




30°
ASEL12D30G




40°
ASEL12D40G




60°
ASEL12D60G










A25°
ASEL12DA25G



A45°
ASEL12DA45G



145°
ASEL12D145G



Technical remarks:
1. Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, sinkhole, bubble, and other defects.
4. When the lamp edge's rubber ring for re-mounting, the roughness of the contact surface between the radiator and the rubber ring is required: Ra0.3, 2.0 μm

C H A N G E						PART		材 質 MATERIAL	透 明 度 TRANSPARENCY	SHEET	UNIT	ASAHI OPTICS LIMITED
						0 ~ 10	±0.05					
E	A/0	2025-10-20	NEW			10 ~ 20	±0.10	設計 DESIGN	PMMA	2/JL	2025-10-20	料号 PART NO: ASEL12D Series
						20 ~ 30	±0.15					
						30 ~ 40	±0.20					
						40 ~ 60	±0.30					
	规格 SPEC	日期 DATE	变更说明 MODIFICATION DESCRIPTION	变更 (CHANGE)	批准 (APPROVE)	公差 DIM	公差 TOL	设计 DESIGN	材料 MATERIAL	透明 TRANSPARENCY	尺寸 SIZE	品名 Product: Extrusion linear lens